

Ordering data		Order No.
Echomax XPS-10F ultrasonic transducer High-frequency ultrasonic transducer designed for a wide variety of liquid and solid applications, for use with approved controllers. Includes integral temperature sensor. Measuring range: min. 0.3 m, max.10 m	C)	7 M L 1 1 7 0 - 0
Mounting thread and facing 1" NPT (ANSI/ASME B1.20.1)	1	
Cable length 5 m (16.40 ft) 10 m (32.81 ft) 30 m (98.43 ft) 50 m (164.04 ft) 100 m (328.08 ft)	B C D E F	
Mounting flange, flush mount None 3" ASME, 150 lb, flat faced 4" ASME, 150 lb, flat faced 6" ASME, 150 lb, flat faced 8" ASME , 150 lb, flat faced (Note: Flange bolting patterns and facings dimensionally correspond to the applicable ASME B16.5, or EN 1092-1, or JIS B 2238 standard.)	A B C D E	
Approvals FM Class I Div. 1	1	
Further designs Please add “-Z” to Order No. and specify Order code(s).	Order code	
Stainless steel tag [69 mm x 50 mm (2.71 x 1.97”)]: Measuring-point number/identification (max. 16 characters) specify in plain text	Y15	
Instruction manual English Note: The Instruction manual should be ordered as a separate line item on the order. Applications Guidelines, multi-language Note: The Applications Guidelines should be ordered as a separate line item on the order. This device is shipped with the Siemens Milltronics manual CD containing the complete instruction manual library.	C) C)	7ML1998-1DU01 7ML1998-5HV61
Accessories Submergence shield kit Easy Aimer 2, with ¾" x 1" NPT PVC coupling Easy Aimer 304, with stainless steel coupling Universal box bracket, mounting kit Channel bracket, wall mount Extended channel bracket, wall mount Channel bracket, floor mount Extended channel bracket, floor mount Bridge channel bracket, floor mount (See Mounting Brackets on page 5/118 for more information.) 1" NPT locknut, plastic	7ML1830-1BH 7ML1830-1AQ 7ML1830-1AU 7ML1830-1BK 7ML1830-1BL 7ML1830-1BM 7ML1830-1BN 7ML1830-1BP 7ML1830-1BQ 7ML1830-1DS	
Split flanges 3", aluminum 3", 304 stainless steel Gasket Kit 3", neoprene 4", aluminum 4", 304 stainless steel Gasket Kit 4", neoprene 6", aluminum 6", 304 stainless steel Gasket Kit 6", neoprene Instruction manual	7ML1830-1AV 7ML1830-1AW 7ML1930-1BF 7ML1830-1BA 7ML1830-1BB 7ML1930-1BG 7ML1830-1BC 7ML1830-1BD 7ML1930-1BH 7ML1998-1EP01	
Refer to page 5/117 for split flanges for XPS-10 transducers.		