

Selection and Ordering data	Order No.
<div>Resistance thermometer for damp rooms</div> <div>stainless steel protective tube</div> <div> <ul style="list-style-type: none"> with one Pt100 measuring resistor 0.1 kg (0.22 kg) with two Pt100 measuring resistors 0.1 kg (0.22 kg) </div>	<div>7MC1027-1AA</div> <div>7MC1027-1AB</div>
<div>Further designs</div> <div>Please add "-Z" to Order No. and specify Order code(s) and plain text.</div>	<div>Order code</div>
<div>Different design (mounting length, protective tube material etc.), specify in plain text.</div> <div>TAG plate made of stainless steel specify TAG No. in plain text</div> <div>Calibration carried out at one point, specify desired temperature in plain text (order equivalent number of times for several calibration points).</div> <div>If optional head transmitters are integrated, please note that all calibration points are located in the set measuring range. If the points are located outside the standard measuring range, a Y11 addition is always required.</div>	<div>Y01</div> <div>Y15</div> <div>Y33</div>
<div>Available ex stock</div>	
<div>To order a temperature transmitter installed in the connection head and transmitters for SIL applications, see "Temperature transmitters for mounting in the connection head" (page 3/79).</div>	
<div>Note:</div> <div>Additional fitting of head mounted transmitter of SITRANS TH series is possible.</div>	