

Selection and Ordering data		Order No.
SITRANS F C Flow sensors		
SITRANS FCS200 sensor, without heating jacket		7 ME 4 5 0 0 -
Sensor size and material		2 D 2 E 1 F
Pressure		K N
Process connection/flange		7 1 7 2 7 3 8 1 8 2 8 3 8 4 8 5
Configuration		1
Transmitter		A
Cable		A
Calibration		1

Description	Order No.
• English	A5E02508199
• German	A5E03082574
• Spanish	A5E03082587
• French	A5E03082581
• Italian	A5E03504933

Spare parts

Description	Order No.
Multiple plug for cable mounting	FDK:083H5056
2 kB SENSORPROM unit (Sensor Serial No. and Order No. must be specified by ordering)	FDK:083H4410

Selection and Ordering data	Order code
Additional information	
Please add “-Z” to Order No. and specify Order code(s) and plain text.	
Pressure testing certificate PED: 97/23/EC	C11
Material certificate EN 10204-3.1	C12
NDT-Penetrant inspection report ISO 3452	C13
Factory certificate according to EN 10204 2.2	C14
Factory certificate according to EN 10204 2.1	C15
Tag name plate, stainless steel	Y17

Accessories

Description	Order No.
Cable with multiple plug	5 m (16.4 ft) FDK:083H3015
Standard blue cable between SIFLOW FC070/MASS 6000 and FCS200,	10 m (32.8 ft) FDK:083H3016
5 x 2 x 0.34 mm ² twisted and screened in pairs.	25 m (82 ft) FDK:083H3017
Temperature range -20 °C ... +110 °C (-4 °F ... +230 °F)	50 m (164 ft) FDK:083H3018
	75 m (246 ft) FDK:083H3054
	150 m (492 ft) FDK:083H3055