




Spare parts - transmitter FCT030

Description	Order No.	
Display and keypad assembly with firewire connection to the transmitter module	A5E03548971	
Sensor interface (Compact). Front end flow calculator and process detection. SIL 3 approved	A5E03549142	
Sensor interface (Remote); barrier unit for high speed digital communication and Ex ib power supply to remote front end DSL module	A5E03549098	
Display lid in painted aluminum with Ex glass plate and o-ring seal	A5E03549344	
Transmitter cassette (active) with SIL approved 4 ... 20 mA output and HART 7.2	A5E03549357	
Transmitter cassette (passive) with SIL approved 4 ... 20 mA output and HART 7.2	A5E03549383	
Bag of loose spare parts; including cable strain relief components, mounting tool, seals and gasket, assorted screws and washers, hex cap nut, blind plugs, and o-rings	A5E03549396	
Power supply 240 V AC, 47 ... 63 Hz 24 ... 90 V DC	A5E03549413	
Blind lid in painted aluminum with o-ring seal	A5E03549429	
I/O assembly Advise Order code F00 to F97 from Selection and Ordering data	A5E03939114	
SensorFlash (1 GB micro SD card)	A5E03915258	

Description	Order No.	
Mounting bracket - FCT030; in painted aluminum for pipe or wall mounting of transmitter FCT030 remote version. Including lock ring, pressure pads and seal cap	A5E03906091	
M12 option for sensor housing in stainless steel. Pre-wired and potted to replace M12 socket in DSL housing	A5E03906095	
M12 option - remote - in painted aluminum. Pre-wired and potted replacement M12 connection for FCT030 transmitter remote version	A5E03906104	
Remote terminal house - M20	A5E03906112	
Remote terminal house - NPT - in painted aluminum for sensor cable termination at FCT030 transmitter remote version. Pre-wired and potted	A5E03906130	

Spare parts - sensor FCS400

Description	Order No.	
Blind lid in painted aluminum with o-ring seal	A5E03549295	
Sensor link insert. Front end flow calculator and process detection. SIL 3 approved	A5E03549191	
Sensor housing metric	A5E03549313	
Sensor housing NPT in painted aluminum	A5E03906080	
Bag of loose parts for sensor; including cable strain relief components, washer, seals, o-rings, and assorted screws	A5E03549324	

Accessories

Description	Order No.	
Bag of glands (metric) in black plastic ¹⁾	A5E03907414	
Bag of glands, (metric) in gray plastic Ex e/i ¹⁾	A5E03907424	
Bag of glands (metric) in AISI 316 SS ¹⁾	A5E03907429	
Bag of glands (metric) in NiPlatedBrass ¹⁾	A5E03907430	
Bag of glands (NPT) in black plastic ²⁾	A5E03907435	
Bag of glands (NPT) in gray plastic Ex e/i ²⁾	A5E03907451	
Bag of glands (NPT) in AISI 316 SS ²⁾	A5E03907467	
Bag of glands (NPT) in NiPlatedBrass ²⁾	A5E03907473	
Standard cable (non-Ex) with M12 plugs, PO insulation and PUR sleeve, gray, -40 ... +80 °C (-40 ... +176 °F)		
• 5 m (16.4 ft)	A5E03914805	
• 10 m (32.8 ft)	A5E03914850	
• 25 m (82 ft)	A5E03914853	
• 50 m (164 ft)	A5E03914859	
• 75 m (246 ft)	A5E03914861	
• 150 m (492 ft)	A5E03914874	
Standard cable (non-Ex) for termination, PO insulation and PUR sleeve, gray, -40 ... +80 °C (-40 ... +176 °F)		
• 5 m (16.4 ft)	A5E03914833	
• 10 m (32.8 ft)	A5E03914849	
• 25 m (82 ft)	A5E03914854	
• 50 m (164 ft)	A5E03914856	
• 75 m (246 ft)	A5E03914864	
• 150 m (492 ft)	A5E03914873	

Description	Order No.	
Standard cable (Ex) with M12 plugs, PO insulation and PUR sleeve, blue, -40 ... +80 °C (-40 ... +176 °F)	A5E03914929 A5E03914962 A5E03914995 A5E03915004 A5E03915074 A5E03915088	
Standard cable (Ex) for termination, PO insulation and PUR sleeve, blue, -40 ... +80 °C (-40 ... +176 °F)	A5E03914945 A5E03914973 A5E03914984 A5E03915015 A5E03915057 A5E03915100	
Service toolkit for field maintenance of transmitter and sensor components. Contains all hand tools necessary for maintenance. Other tools may be required for installation.	A5E03722877	
Heating Jacket, indoor use, 200 °C (392 °F) max. temperature. Complete with 5 m (16.4 ft) high temperature cable fitted. Dedicated plug connection to controller	A5E03830623 A5E03830624 A5E03830625 A5E03830626	
• DN 15 electric • DN 25 electric • DN 50 electric • DN 80 electric		
Heating jacket controller, IP65. Digital display for 0 ... 200 °C (32 .. 392 °F) control setpoint	A5E03839193 A5E03839194	

¹⁾ 2 pcs M20; 1 pce M25 with single and dual cable inserts
²⁾ 2 pcs ½" NPT; 1 pce ½" NPT with single and dual cable inserts

Description	Dimension	Order No.
Mating parts for hygienic fittings DIN 11851 Includes: • 2 unions • 2 mating parts (for welding in) • 2 EPDM gaskets	DN 10	FDK:085U1016
	DN 15	FDK:085U1017
	DN 25	FDK:085U1019
	DN 32	FDK:085U1020
	DN 40	FDK:085U1021
	DN 50	FDK:085U1022
	DN 65	FDK:085U1023
Mating parts for hygienic clamp ISO 2852 Includes: • 2 clamps • 2 mating parts • 2 EPDM gaskets	25 mm	FDK:085U1029
	40 mm	FDK:085U1031
	50 mm	FDK:085U1032
2 EPDM gaskets with collar for mounting set DIN 11851	DN 10	FDK:085U1006
	DN 15	FDK:085U1007
	DN 25	FDK:085U1009
	DN 32	FDK:085U1010
	DN 40	FDK:085U1011
	DN 50	FDK:085U1012
	DN 65	FDK:085U1013