

**Selection and Ordering data**

Order No.

**The Probe**

Short-range integrated ultrasonic level transmitter, ideal for liquids and slurries in open or closed vessels

C) **7ML1201-** **00****Measuring range**

5 m (16.40 ft)

**1****Transducer/Process connection**

PVDF copolymer, 2" NPT [(Taper), ANSI/ASME B1.20.1]

PVDF copolymer, R 2" [(BSPT), EN 10226]

PVDF copolymer, G 2" [(BSPP), EN ISO 228-1]

PVDF copolymer, 4" Sanitary mounting, 3A approved

**E****F****G****H****Model/Approval**

3 Wire, 24 V DC, CSA, CE, FM

2 Wire, 24 V DC, CE

**E****F****Additional instruction manual**

3 Wire, 24 V model, Multi-language manual

2 Wire model, Multi-language manual

This device is shipped with the Siemens Milltronics manual CD containing ATEX Quick Starts and instruction manuals.

C) **7ML1998-1GD62**C) **7ML1998-1GC62****Accessories**

Tag, stainless steel, 12 x 45 mm (0.47 x 1.77"), one text line suitable for enclosures

Universal Box Bracket Mounting kit

Sanitary 4" mounting clamp

Power Supply, 24 V DC, 200 mA for 2 probes (105 to 125 V AC input)

C) **7ML1930-1AA**

Power Supply, 24 V DC, 100 mA for 1 probe (105 to 125 V AC input)

C) **7ML1930-1AB**

2" NPT locknut, plastic

2" BSPT locknut, plastic

Plastic M20 cable gland with metal locknut

**7ML1830-1DT****7ML1830-1DQ****7ML1930-1DB**

C) Subject to export regulations AL: N, ECCN: EAR99