

3RT, 3RH, 3TB, 3TC, 3TH, 3TK Contactors for Special Applications

Contactors with Extended Operating Range $0.7 \dots 1.25 \times U_s$, for Railway Applications

3RT10 motor contactors, 5.5 ... 45 kW

Technical specifications

Contactor	Type		3RT10 17	3RT10 2.	3RT10 3.	3RT10 4.
Magnetic coil operating range	AC/DC		$0.7 \dots 1.25 \times U_s$			
Power consumption of the magnetic coils			For cold coil and $1.0 \times U_s$			
Contactors with series resistor	Closing	W	11	23	46	78
	Closed	W	4	7	14	23
Contactors without series resistor	Closing	W	2.3	4.2	--	--
	Closed	W	2.3	4.2	--	--
Upright mounting position			Standard version	3RT10 2.-3K.40: Special version required 3RT10 2.- 3K.44-OLA0: Special version required	--	--

All specifications and technical specifications not mentioned here are identical to those of the standard contactors.

Contactor	Type		3RT10 2.	3RT10 3.	3RT10 4.
3RT10 contactors with contactor control unit					
Magnetic coil operating range			$0.7 \dots 1.25 \times U_s$		
Power consumption for cold coil and $1.0 \times U_s$		W	6	15	19
Closing = closed					
Upright mounting position			Special version required	--	

All specifications and technical specifications not mentioned here are identical to those of the standard contactors.