

**Temperature transmitter
SITRANS TH300**

for installation in the connection
head type B (DIN 43729)
2-wire connection 4 ... 20 mA,
communication-capable acc. to
HART, with electrical isolation

- Without explosion protection ▶ **7NG3212-0NN00**
C)
- With explosion protection;
type of protection:
"Intrinsic safety" and EEx n
 - acc. to ATEX ▶ **7NG3212-0AN00**
C)
 - acc. to FM (cFM_{US}) ▶ **7NG3212-0BN00**
C)

Further designs

Please add "-Z" to Order No. and
specify Order code(s)

Customer-specific setting of oper-
ating data (specify operating data
in plain text)

Y01

with test protocol (5 measuring
points)

C11

Accessories

Order No.

**CD for measuring instruments
for temperature** ▶ **A5E00364512**
G)

with documentation in German,
English, French, Spanish, Italian,
Portuguese and SIPROM T
parameterization software

HART modem

- With RS 232 connection ▶ **7MF4997-1DA**
D)
- With USB connection ▶ **7MF4997-1DB**
D)

**SIMATIC PDM operating
software**

See Section 9

**DIN rail adapters for head
transmitters** ▶ **7NG3092-8KA**

(Quantity delivered: 5 units)

▶ Available ex stock.

C) Subject to export regulations AL: N, ECCN: EAR99.

D) Subject to export regulations AL: N, ECCN: EAR99H.

G) Subject to export regulations AL: N, ECCN: 5D992B1.

Power supply units see "SITRANS I supply units and isolation amplifiers".