

Selection and Ordering Data

Description	7MB2021	7MB2011	7MB2011 Ex	2 years (qty)	5 years (qty)	Order No.
Analyzer part						
O-ring (stub)	x	x	x	2	4 D)	C71121-Z100-A159
O-ring	x			1	2 D)	C74121-Z100-A6
O-ring (measuring head)	x	x	x	2	4 D)	C79121-Z100-A32
Spacer	x	x	x	-	1 D)	C79451-A3277-B22
Sample cell, stainless steel, mat. no. 1.4571; non-flow-type compensation branch	x	x	x	-	1 D)	C79451-A3277-B535
Sample cell, tantalum, non-flow-type compensation branch	x	x	x	-	1 D)	C79451-A3277-B536
Sample cell, stainless steel, mat. no. 1.4571; flow-type compensation branch	x	x	x	-	1 D)	C79451-A3277-B537
Sample cell, tantalum, flow-type compensation branch	x	x	x	-	1 D)	C79451-A3277-B538
Measuring head, non-flow-type compensation branch	x	x	x	1	1 D)	C79451-A3460-B525
Measuring head, flow-type compensation branch	x	x	x	1	1 D)	C79451-A3460-B526
Magnet connection plate	x	x	x	-	1	C79451-A3474-B606
Temperature sensor	x	x	x	-	1 D)	C79451-A3480-B25
Heating cartridge	x	x	x	-	1 D)	W75083-A1004-F120
Sample gas path						
Pressure switch (sample gas)	x			1	2 D)	C79302-Z1210-A2
Flow meter (version with pump only)	x			1	2 D)	C79402-Z560-T1
Restrictor, stainless steel, mat. no. 1.4571; hose gas path	x			2	2 D)	C79451-A3480-C10
Restrictor, titanium, pipe gas path	x	x	x	2	2 D)	C79451-A3480-C37
Reference gas path, 3000 hPa	x	x	x	1	1 D)	C79451-A3480-D518
Capillary tube, 100 hPa, connection set	x	x	x	1	1 D)	C79451-A3480-D519
Restrictor, stainless steel, mat. no. 1.4571; pipe gas path	x	x	x	1	1 D)	C79451-A3520-C5
Electronics						
Temperature controller - electronic, 230 V AC		x	x	-	1 D)	A5E00118527
Temperature controller - electronic, 115 V AC		x	x	-	1 D)	A5E00118530
Fusible plug (device fuse)			x	1	2 D)	A5E00061501
Front plate with keyboard	x			1	1 D)	C79165-A3042-B505
Temperature controller	x	x	x	-	1 D)	C79451-A3474-B56
Motherboard, with firmware: see spare parts list	x	x	x	-	1	
Adapter board, LCD/keyboard	x	x		1	1 D)	C79451-A3474-B605
LC display	x	x		1	1 D)	W75025-B5001-B1
Connector filter	x	x	x	-	1 D)	W75041-E5602-K2
Temperature fuse (heated version only)		x		-	1	W75054-T1001-A150
Fusible plug, T 0.63/250 V	x	x	x	2	4 D)	W75054-L1010-T630
Fusible plug, 1 A, 110/220 V	x	x	x	2	4 D)	W75054-L1011-T100
Fusible plug, 2,5 A, 250 V		x	x	2	3 D)	W75054-L1011-T250

D) Subject to AL export regulations: 91999, ECCN: N

If the OXYMAT 6 is supplied with a specially cleaned gas path for high oxygen context ("Cleaned for O₂ service"), please ensure that you specify this when ordering spare parts. This is the only way to guarantee that the gas path will continue to comply with the special requirements for this version.