

Selection and Ordering Data		Order No.	
In situ LDS 6 gas analyzer Sensor pair (cross duct), sensor type CD 6C		D) 7MB6023 -	00 -
Ex-protection without	Ignition protection n.a.	0	
Sensor type CD 6C	Component H ₂ O in Cl ₂	M	
Purging mode, process side No purging	Sensor side N ₂ , 6 ... 20 l/min; incl. outlet needle valve	B	
N ₂ elevated flow 1 ... 100 l/min incl. inlet test valve	N ₂ , 6 ... 20 l/min; incl. outlet needle valve	F	
Flange version Stainless steel (SS 2343/316L), window made of borosilicate glass DN 80/PN 16 Customized process interface			0 9
Hybrid cable No hybrid cable Standard length	Length [m] 5 10 25 50		X A B E H Z
Customized length	only > 50 m		Z
Loop cable No loop cable Standard length	Length [m] 5 10 25		X A B E Z
Customized length	only > 25 m		Z
Language (supplied documentation) German English French Spanish Italian			0 1 2 3 4

D) Subject to export regulations AL: 9I999, ECCN: N

Selection and Ordering Data		Order code	
<i>Further models</i>			
Please add „-Z“ to Order No. and Order code			
Hybrid cable, customized length		P1Y	
Loop cable, customized length		Q1Y	
TAG label, customer-defined inscriptions		Y30	
<i>Additional units</i>		Order No.	
CD6-C alignment kit (adapter)		A5E00835004	